



KLEMMEN



MINIKLEMMEN

GEALVANISEERD

nr.	formaat	verpakt per
6005008	8	50
6005009	9	50
6005010	10	50
6005011	11	50
6005012	12	50
6005013	13	50
6005014	14	50
6005015	15	50



MINIKLEMMEN

RVS

nr.	formaat	verpakt per
6026008	8	50
6026009	9	50
6026010	10	50
6026011	11	50
6026012	12	50
6026013	13	50
6026014	14	50
6026015	15	50



WORMSCHROEFKLEMMEN

RVS

Let op: W5 kwaliteit

Volledig roestvrijstalen W5 slangklemmen. Roestvrijstalen band W5 (AISI 316). Roestvrijstalen huis W5 (AISI 316). Roestvrijstalen schroef W5 (AISI 316). Conform DIN 3017 en SMS 2298

nr.	inw. /uitw.	verpakt per
6011008	8/16	50
6011013	12/20	50
6011015	16/25	50
6011019	20/32	50
6011026	25/40	50
6011038	32/50	50
6011044	40/60	50
6011050	50/70	50
6011058	60/80	Los
6011068	70/90	Los
6011077	80/100	Los
6011087	90/110	Los



WORMSCHROEFKLEMMEN

GEALVANISEERD

Conform DIN 3017 en SMS 2298;

schroef met zeskant. Band met gesloten fraising en voorzien van afgeronde kanten, zodat beschadiging van de slang wordt voorkomen. Gealvaniseerd en gechromatiseerd. Voldoet aan de strengste eisen.

nr.	inw. /uitw.	verpakt per
6000008	8/ 14	50
6000011	11/17	50
6000013	13/20	50
6000015	15/25	50
6000019	19/32	50
6000026	26/40	50
6000032	32/44	50
6000038	38/50	50
6000044	44/60	50
6000050	50/70	50
6000058	58/80	Los
6000068	68/90	Los
6000077	77/100	Los
6000087	87/110	Los



LEIDINGKLEMMEN

RVS

Roestvrijstalen band W4 (AISI) Voorzien van EPDM rubber. Bandbreedte: 12 mm

nr.	klembereik	verpakt per
6051006	6	100
6051008	8	100
6051010	10	50
6051013	13	50
6051016	16	50
6051021	21	50
6051029	29	50
6051035	35	50
6051045	45	50
6051053	53	50



LEIDINGKLEMMEN

GEGALVANISEERD

Voorzien van EPDM rubber.
Bandbreedte: 12 mm (conform DIN 3016)

nr.	klembereik	verpakt per
6054006	6	100
6054008	8	100
6054010	10	50
6054013	13	50
6054016	16	50
6054021	21	50
6054029	29	50
6054035	35	50
6054050	50	50



SUPER STRENGHT SLANGKLEMMEN

1- DELIG GEGALVANISEERD

Eéndelige zware slangklemmen, voorzien van een M8 bout.

Materiaal: gegalvaniseerd volgens DIN 50941

Staalband breedte: 20 mm

Staalbanddikte: 1,5 mm

nr.	inw. /uitw.	staalbandbreedte
6200040	40/43	M8 20
6200044	44/47	M8 20
6200048	48/51	M8 20
6200052	52/55	M8 20
6200056	56/59	M8 20
6200060	60/63	M8 25
6200064	64/67	M8 25
6200068	68/73	M8 25
6200074	74/79	M8 25
6200080	80/85	M8 25
6200086	86/91	M8 25
6200092	92/97	M8 25
6200098	98/103	M8 25
6200104	104/112	M8 25
6200113	113/121	M8 25
6200122	122/130	M8 25
6200131	131/139	M8 25
6200140	140 /148	M8 25
6200149	149/161	M8 25
6200162	162/174	M8 25
6200175	175/187	M8 25
6200188	188/200	M8 25
6200201	201/213	M8 25
6200214	214/226	M8 25
6200227	227/234	M8 25
6200240	240/252	M8 25



SUPER STRENGHT SLANGKLEMMEN

1- DELIG RVS W5 KWALITEIT

Eéndelige zware slangklemmen, voorzien van een M8 / M6 bout.

Materiaal band: RVS AISI 316, Bout: M8 A4, Moer: M8 A4 / M6 A4

Staalbanddikte: 1,5 mm

nr.	inw. /uitw.	staalbandbreedte
6400026	26/28	M6 20
6400029	29/31	M6 20
6400032	32/35	M6 20
6400036	36/39	M6 20
6400040	40/43	M6 20
6400044	44/47	M6 20
6400048	48/51	M8 20
6400052	52/55	M8 20
6400056	56/59	M8 20
6400060	60/63	M8 25
6400063	64/67	M8 25
6400067	68/73	M8 25
6400074	74/79	M8 25
6400080	80/85	M8 25
6400086	86/91	M8 25
6400092	92/97	M8 25
6400095	98/103	M8 25
6400104	104/112	M8 25
6400110	113/121	M8 25
6400122	122/130	M8 25
6400132	131/139	M8 25
6400142	140/148	M8 25
6400152	149/161	M8 25
6400162	162/174	M8 25