



APPLICATION

Softwall rubber hose suitable for conveying hot water mixed with cooling liquids.

Standards: DIN 73411

- *Temperature range:* -40°C +120°C

CONSTRUCTION

- *Tube:* black, smooth, heat resistant EPDM rubber.
- *Reinforcement:* high strength synthetic textile plies.
- *Cover:* black, abrasion, heat and ageing resistant EPDM rubber.
- *Surface:* smooth fabric finished.
- *Branding:* embossed 'H.T.-RADIATORE - -40°C +120°C - d.i. - DIN 73411'



DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESS. ESERCIZIO WORKING PRESSURE		PRESS. SCOPPIO BURST PRESSURE		LUNGHEZZA LENGTH	
22	7/8"	28	1.3/32"	0.33	0.22	4	60	12	180	1/20	3.28/65.5
25	1"	32	1.1/4"	0.42	0.28	4	60	12	180	1/20	3.28/65.5
28	1.3/32"	36	1.13/32"	0.46	0.31	4	60	12	180	1/20	3.28/65.5
30	1.3/16"	38	1.1/2"	0.58	0.39	4	60	12	180	1/20	3.28/65.5
32	1.1/4"	40	1.9/16"	0.62	0.42	4	60	12	180	1/20	3.28/65.5
35	1.3/8"	43	1.11/16"	0.67	0.45	4	60	12	180	1/20	3.28/65.5
38	1.1/2"	46	1.13/16"	0.82	0.55	4	60	12	180	1/20	3.28/65.5
40	1.9/16"	49	1.15/16"	0.86	0.58	4	60	12	180	1/20	3.28/65.5
42	1.21/32"	51	2"	0.90	0.61	4	60	12	180	1/20	3.28/65.5
45	1.3/4"	54	2.1/8"	1.02	0.69	4	60	12	180	1/20	3.28/65.5
48	1.7/8"	58	2.9/32"	1.07	0.72	4	60	12	180	1/20	3.28/65.5
50	1.31/32"	60	2.3/8"	1.13	0.76	4	60	12	180	1/20	3.28/65.5
55	2.5/32"	65	2.9/16"	1.32	0.89	4	60	12	180	1/20	3.28/65.5
60	2.3/8"	70	2.3/4"	1.43	0.96	4	60	12	180	1/20	3.28/65.5