

## Fuel Hose ISO 7840 A1



Hardwall corrugated cover rubber fuelhose suitable for loading Diesel, bio-diesel and unleaded fuel for marine pleasure craft with inboard engine up to 24m length. Provided with standard ISO 7840 A1.

### Technical Information

Standards	:	ISO 7840 A1 SAE J 1527:2011 USCG A1 Approved RINA & Lloyd's
Temperature range	:	-20 °C tot 80 °C
Construction	:	
Tube	:	Black, smooth, petroleum products up to 50% aromatic content resistant NBR Rubber. Bio-diesel and unleaded fuel up to 15% oxygen compound resistant.
Reinforcement	:	High strength synthetic textile plies.
Cover	:	Black, abrasion, heat, fuels, ozone, marine agents resistant self-extinguishing CR/NBR Rubber
Surface	:	Smooth fabric finished.
Branding	:	Red transfer tape lettering.

“t” CARBOPOMP MARINE FUEL ISO 7840:2021 A1 E10/B10 COMPATIBLE CE - SAE J 1527:2011 USCG A1 - RINA - LLOYD'S REGISTER (ANNO-DIA.INT)

Article number	Internal diameter		Thickness		Weight [kg/m]	Burst pressure [bar]	Bending radius [mm]	Length [m]
	[mm]	[inches]	[mm]	[inches]				
3330032	32	1 1/4"	5	3/16"	0,90	>10	50	20
3330038	38	1 1/2"	5	3/16"	1,05	>10	60	20
3330050	51	2"	5	3/16"	1,35	>10	75	20