

Fuel Hose ISO 7840 A1



Softwall rubber hose suitable for loading Diesel, bio-diesel and unleaded fuel for marine pleasure craft with inboard engine up to 24m length. Provided with standard ISO 7840 A1.

Technical Information

Standards	:	ISO 7840 A1 SAE J 1527:2011 USCG A1 Approved RINA & Lloyd's
Temperature range	:	-20 °C tot 80 °C
Construction	:	
Tube	:	Black, smooth, petroleum products up to 50% aromatic content resistant NBR Rubber. Bio-diesel and unleaded fuel up to 15% oxygen compound resistant.
Reinforcement	:	High strength synthetic textile plies.
Cover	:	Black, abrasion, heat, fuels, ozone, marine agents resistant self-extinguishing CR/NBR Rubber
Surface	:	Smooth fabric finished.
Branding	:	Red transfer tape lettering.

“†” CARBOPOMP MARINE FUEL ISO 7840:2021 A1 E10/B10 COMPATIBLE CE - SAE J 1527: 2011 USCG A1 - RINA - LLOYD'S REGISTER (ANNO-DIA.INT)

Article number	Internal diameter		External diameter		Weight [kg/m]	Burst pressure [bar]	Bending Radius [mm]	Length [m]
	[mm]	[inches]	[mm]	[inches]				
3330006	6	1/4"	15	9/16"	0,26	>14	30	40
3330008	8	4/16"	16	5/8"	0,27	>14	45	40
3330010	10	3/8"	18	3/4"	0,30	>14	55	40
3330125	12	1/2"	21	7/8"	0,43	>10	70	40
3330016	16	5/8"	25	1"	0,50	>10	90	40
3330019	19	3/4"	29	1 5/32"	0,64	>10	130	40
3330025	25	1"	37	1 15/32"	0,87	>10	250	40