



- Voltage Rating : DC32V or less
- Interrupting Rating: 1000A @32VDC
- Operating Temperature Range : -40°C to +125°C
- Complies with  
SAE J1284 / JASOD612 / ISO 8820-3
- Materials :
  1. Zinc Alloy
  2. Plastic

Item No.	Ampere	Color
ATS 1	1 A	Black
ATS 2	2 A	Grey
ATS 3	3 A	Purple
ATS 4	4 A	Pink
ATS 5	5 A	Orange
ATS 7.5	7.5 A	Dark Brown
ATS 10	10 A	Red
ATS 15	15 A	Blue
ATS 20	20 A	Yellow
ATS 25	25 A	White
ATS 30	30 A	Green

Test Current	Opening Time	
	Min.	Max.
110%	100hrs.	---
135%	0.75 s	600 s
160%	0.25 s	50 s
200%	0.15 s	5 s
350%	0.04 s	0.5 s
600%	0.02 s	0.1 s



**BEZOEKADRES**  
Melkrijder 14  
3861 SG Nijkerk

**POSTADRES**  
Postbus 1031  
3860 BA Nijkerk

**CONTACT**  
T: + 31 (0)33 245 78 86  
F: + 31 (0)33 245 47 83

I: [www.dgrubberholland.nl](http://www.dgrubberholland.nl)  
E: [info@dgrubberholland.nl](mailto:info@dgrubberholland.nl)