

SEAWATER HOSE

HOT WATER + 120°C

This multipurpose S/D hose is suitable for hot water, seawater, neutral acid and basic solutions, paints with water and ketones basis and for solvents with esters.

TECHNICAL INFORMATION

Rubberhoses : For steam and hot water
 Purpose : S/D Suction and Delivery
 Working Pressure : 10 Bar
 Temperature : -40 °C / 120 °C

Tube : Smooth black conductive rubber, resistant to heat and paints
 Reinforcement : High tensile textile plies, helix wire embedded
 Cover : Black, smooth conductive rubber, resistant to abrasion, ozone, weather and heat. Fabric impression

Working Pressure : 10 bar
 Bursting Pressure : 30 bar

Marking : THOR HOT WATER +120 °C - WP 10 BAR (red letters)

SIZES

Article number	Inner diameter mm	Outer diameter mm	Wall thickness mm	weight Kg / m	Vacuum bar	Bending radius mm
3351016	16	26	5,0	0,44	0,8	97
3351020	19	29	5,0	0,59	0,8	115
3351025	25	35	5,0	0,72	0,8	150
3351032	32	42	5,0	0,89	0,8	190
3351038	38	49	5,5	1,16	0,8	230
	40	51	5,5	1,25	0,8	240
3351050	51	62	5,5	1,45	0,8	300
	63	75	6,0	2,00	0,8	380
	76	90	7,0	2,35	0,8	450
	102	116	7,0	3,80	0,8	600