

DKIT - DG Rubber Holland Kit 310ml



This adhesive is a high-quality, gap-filling, fast-curing D4 construction adhesive based on modified polyurethane. It cures through a reaction with moisture in the substrate, creating a strong, durable and waterproof bond. It offers excellent adhesion, without a primer to virtually all damp substrates, including wood, metal, stone, concrete, plastic, rubber, insulation material, mineral wool, glass wool and fiber-cement boards.

Technical information

Base	:	Modified Polyurethane
Density	:	1,48 g/ml
Odour	:	None / neutral
Shrinkage	:	None
Curing	:	Moisture-curing
Skin formation time	:	5 minutes (at 23 °C 50% RH. (Relative Humidity))
Curing-time	:	80% after 20 min. 100% after 1 uur ((at 23 °C 50% RH.))
Tensile Strength	:	11 N/mm ² after 24 hours
Water resistance	:	D4
Flow resistance	:	< 2mm
Application temperature	:	+5 °C - +40 °C
Certi	:	

Frost resistance during transport: Down to -15 °C

Shelf life : in unopened original packaging, stored in a dry place at between 5 °C and 25 °C, and protected from moisture, the product shelf life of up to 15 month from the date of manufacture. Brief exposure to temperatures down to -15 °C, or exposure during transport, is permitted.