

## FLAT PVC CABLE

Flat PVC cable with red and black conductors:

2 x 0,75 mm<sup>2</sup>, 2 x 1,5 mm<sup>2</sup>, 2 x 2,5 mm<sup>2</sup>,



### CONSTRUCTION

Conductor		: Fine Stranded Annealed Copper Wires
Conform		: IEC/BS/TS/EN 60228, VDE 0295 Class5
Insulation		: PVC (Polyvinyl Chloride) Black / Red
Outer Sheath		: PVC Black

Article number	No of core	Cross Section [mm <sup>2</sup> ]	Conductor (Cu) (stranded)	Sheath Thicknes (nom. mm) [mm]	Mean overall Dimensions		Roll Length [m]
					Lower Limit [mm]	Upper Limit [mm]	
33667075	2	0,75	24 x 0,19	0,6	3,7 x 6,0	4,5 x 7,5	100
336710	2	1,00	30 x 0,19				100
336715	2	1,50	30 x 0,24	0,7	4,2 x 7,0	5,2 x 8,6	100 & 500
336725	2	2,50	50 x 0,24	0,8	4,7 x 7,5	5,7 x 10,2	100 & 500

### TECHNICAL AND ELECTRICAL PROPERTIES (20 °C)

Operating Voltage	: 300 / 500 V
Test Voltage	: 2 kV
Temperature Range	: 70 °C
Min. Bending Radius	: 6 x Cable Diameter
Flame Propagation	: IEC/EN/BS/DIN 60332-1-2,

