


## H05VV-F Round PVC Cable Black



Cable : PVC insulated multi core flexible installation and automotive cables

1) Conductor : Flexible plain copper, massive

Construction : 2) PVC insulation  
4) PVC Sheath

According to EN 50525-2-11 and IEC 60227.5

Temperature range : -15 °C up to 60 °C

Max conductor Temperature : 50 C

Maximum Voltage : 300/500V

Test Voltage (AC) : 2 kV

Cable Marking : H05VV-F \_\_mm<sup>2</sup> BS6500 jaartal

Minimum bending radius : 5 x D

Core insulation color : 2 cores ; Black / Red  
3 cores ; Black / Red / White,  
5 cores ; Brown / Grey / Red / White / Yellow



STANDARD  
TS EN 50525 2-11

## TECHNICAL AND ELECTRICAL PROPERTIES PVC BLACK

Article number	Cores	Quadrature [mm <sup>2</sup> ]	intersection [mm]	iR @ 20 °C [Ω/km]	Current [A]	Weight Cable [kg/km]	Roll Length [m]
30-29450	2	0,75	6,20	26,00	8	54,80	100
30-29484	2	1,50	7,50	13,30	10	84,80	100
30-29485	2	2,50	9,10	7,98	16	129,00	100
30-29452	3	0,75	6,60	26,00	8	65,05	100
30-29468	3	1,50	8,20	13,30	10	107,00	100
30-29478	3	2,50	9,90	7,98	16	161,00	75
30-29525	5	2,50	12,00	7,98	16	249,00	50

